

SPECIFICATIONS

8000 series

Pocket-Size Mobile Computer



		8000	8001	8062	8071
Communication	Options	Batch		BT Class 2 compliance	IEEE 802.11 b/g
	Serial	IrDA (115.2 Kbps)			
	Coverage ¹ line of sight	30 cm / 12 in.		50 m / 164 ft.	350 m / 1148 ft.
Performance	CPU	16-bit			
	Program memory	2MB flash			
	Data memory	2MB SRAM	2MB/4MB SRAM	2MB SRAM	
	Main battery	2 AAA alkaline	Li-ion 3.7V, 700 mAh		
	Backup battery	Rechargeable lithium 3.0V, 7.0 mAh			
	Working time ²	100 hours		36 hours	22 hours ³
	Data retention	30 days			
Data capture	Barcode reader	Linear imager / Laser			
Physical characteristics	Display	LCD 100 × 64 with LED backlight			
	Keypad	21 rubber keys with white LED backlight			
	Alert	Dual-color LED, vibrator, volume-programmable beeper			
	Dimensions L x W x H	122 × 56 × 23 mm 4.8 × 2.2 × 0.9 in.	122 × 56 × 32 mm 4.8 × 2.2 × 1.25 in.	143 × 57 × 35 mm 5.6 × 2.25 × 1.4 in.	
	Weight laser, including battery	123 g / 4.4 oz.	120 g / 4.2 oz.	125 g / 4.4 oz.	166 g / 5.9 oz.
User environment	Operating temperature	-10° to 60°C / 14° to 140°F			
	Storage temperature	-20° to 70°C / -4° to 158°F			
	Humidity non-condensed	Operating: 10% to 90% / Storage: 5% to 95%			
	Impact resistance	1.2 m / 4 ft. drop (5 drops on each side)			
	Electrostatic discharge	±15kV air discharge / ±8kV direct discharge			
EMC regulation	BSMI, CE, C-Tick, FCC, IC	CE, FCC	BSMI, CE, C-Tick, FCC, IC, MIC, NCC, SRMC, TELEC		
Programming	CiperLab Power Suite FORGE Application Generator including data transmission OCX, STREAM Wireless Studio, MIRROR Terminal Emulation, BLAZE C Compiler and BASIC Compiler				
Accessories	USB or RS232 communication cradle (8000 only), charging and communication cradle, modem cradle, Ethernet cradle, GSM/GPRS cradle (GSM900/1800), 4-slot battery charger, USB cable, RS232 cable, AC/DC adapter				
Acoustic coupler 8021 available in US	Data rate/format: 1200, O/E/N, 7/8, 1/2 stop bits Sound frequency: 1.2 KHz ±5%, 2.2 KHz ±5% Modulation type: Bell202/FSK				
Warranty	1 year				

¹ Effective coverage depends on user environment and equipment deployment. It is highly recommended to conduct a site survey before actual deployment.

² Based on one standard laser scan per five seconds with backlight off. ³ Depending on network traffic load.

ACCESSORIES



Communication Cradle



Charging and Communication Cradle




Modem Ethernet Cradle



GSM/GPRS Cradle (GSM900/1800)



4-Slot Battery Charger



©2009 CiperLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.



HEADQUARTERS
CiperLab Co., Ltd.
12F, 333 Dunhua S. Rd., Sec. 2
Taipei, Taiwan 10669
Tel +886 2 8647 1166
Fax +886 2 8732 3300
www.ciperlab.com

CiperLab China
Suite 1305, 1065A, Jaojiabang Rd.
Xuhui District, Shanghai,
China 200030
Tel +86 21 3368 0288
Fax +86 21 3368 0286

CiperLab USA
2552 Summit Avenue
Plano, Texas USA 75074
Tel +1 469 241 9779
Toll Free 888 300 9779
Fax +1 469 241 0697

CiperLab Central Europe
Willicher Damm 143-145
41066 Mönchengladbach
Germany
Tel +49 2161 56230 0
Fax +49 2161 56230 22